D37EX/PX-23

Standard and Optional Equipment

ENGINE AND RELATED PARTS

| Komatsu SAA4D95LE-6 turbocharged common rail direct injection diesel engine | • |
|---|---|
| EU Stage IIIB/EPA Tier 4 interim compliant | • |
| Fuel pre-filter (10 micron) and fuel filter (2 micron) | • |
| Exhaust pipe with elbow | • |
| Intake pipe with rain cap | • |
| Engine cooling fluid corrosion resistor | • |
| Alternator 24 V/60 A | • |
| Starter motor 4,5 kW/24 V | • |
| Batteries 92 Ah/2 × 12 V | • |
| Fuel tank inlet strainer | • |
| Intake pipe with air pre-cleaner | 0 |
| | |

SERVICE AND MAINTENANCE

| Swing-out hydrostat-driven radiator fan with reversing function | • |
|---|---|
| Dry type air cleaner, double element with dust indicator and evacuator | • |
| Water separator | • |
| Multi-function video compatible colour monitor with Equipment Management and Monitoring System (EMMS) and efficiency guidance | • |
| KOMTRAX [™] – Komatsu wireless monitoring system | • |
| Komatsu CARE | • |
| Tool kit | • |

SAFFTY FOUIPMENT

| JAFETT EQUIFMENT | |
|---|---|
| Steel cab, meets ISO 3471 and SAE J1040, APR88 ROPS standards, as well as ISO 3449 FOPS standards | • |
| Horn | • |
| Locks, filter caps and covers | • |
| Back-up alarm | • |
| Rear view camera system | • |
| Fire extinguisher | C |

TRANSMISSION AND BRAKES

| Electronically controlled HST | • |
|------------------------------------|---|
| Palm lever steering control (PCCS) | • |
| Quick shift selection system | • |
| Variable speed mode | • |
| Reverse speed presets | • |
| Combined decelerator/brake pedal | • |

CABIN

| Air suspension seat: fabric, reclining, heated, high backrest | • |
|---|---|
| Seat belt with visible alert | • |
| High mount footrest | • |
| Air conditioner | • |
| Radio | • |
| Auxiliary input (MP3 jack) | • |
| 2 × 12 Volt power supply (120 W) | • |
| 1 × 24 Volt power supply | • |
| Viscous cab mounts | • |
| Rear-view mirror (inside cab) | • |
| Wiper front window | • |
| Wiper rear window | • |
| Wipers doors | • |
| Cup holder | • |
| | |

ATTACHMENTS

| Front pull hook | • |
|-------------------------|---|
| Hitch (not with ripper) | • |

UNDERCARRIAGE

| Single grouser heavy-duty shoes (EX: 400 mm; PX: 600 mm) | • |
|---|---|
| Komatsu PLUS link assembly | • |
| Track roller guard, centre and end section | • |
| Full length track roller guard | 0 |
| Single grouser heavy-duty shoes 460 mm (EX) | 0 |

| Air suspension seat: fabric, reclining, heated, high backrest | • |
|---|---|
| Seat belt with visible alert | _ |
| Seat beit with visible alert | _ |
| High mount footrest | • |
| Air conditioner | • |
| Radio | • |
| Auxiliary input (MP3 jack) | • |
| 2 × 12 Volt power supply (120 W) | • |
| 1 × 24 Volt power supply | • |
| Viscous cab mounts | • |
| Rear-view mirror (inside cab) | • |
| Wiper front window | • |
| Wiper rear window | • |
| Wipers doors | • |
| Cup holder | • |
| | |

DOZER EQUIPMENT

| 1,91 m³ PAT blade (EX) | 0 |
|---|---|
| 2,13 m ³ PAT blade (PX) | 0 |
| 1,95 m ³ narrow PAT blade (PX) | 0 |
| Multishank parallelogram ripper (EX only) | 0 |

LIGHTING SYSTEM

Working lights, 3 cab roof front, 2 cab roof rear

HYDRAULIC SYSTEM

| Hydraulics for dozing blades | • |
|------------------------------|---|
| Mono lever blade control | • |
| Hydraulics for ripper | 0 |

AUTOMATIC MACHINE CONTROL

| Komatsu-Topcon Plug & Play provisions | • |
|--|---|
| Komatsu-Topcon machine control systems | 0 |

Further equipment on request

- standard equipment
- optional equipment

Your Komatsu partner:



Komatsu Europe **International NV**

Mechelsesteenweg 586 B-1800 VILVOORDE (BELGIUM) Tel. +32-2-255 24 11 Fax +32-2-252 19 81

www.komatsu.eu

EENSS20060 07/2013

Materials and specifications are subject to change without notice. **KOMATSU** is a trademark of Komatsu Ltd. Japan.