

CRAWLER DOZER

STANDARD EQUIPMENT

Cab

- Suspension seat: fabric, reclining, high backrest, turnable
- Seat belt
- Headrest
- High mount footrest
- Palm lever steering control (PCCS)
- Mono lever blade control
- Air conditioner
- Heated rear window
- Pre radio installation kit (12 V, antenna, loudspeakers)
- Decelerator pedal
- Electronic monitor panel
- Viscous cab mounts
- Fenders
- Rear-view mirror (inside cab)
- Sun visor (rear window)
- Cup holder
- Lunch box holder

Undercarriage

- Single grouser shoes (EX: 610 mm / PX: 910 mm)
- Heavy-duty link assembly, sealed and lubricated
- Full length track roller guard (EX)
- Track roller guard, centre and end section (PX)
- Segmented sprockets
- Fixed track rollers
- Hydraulic track adjusters

Control systems

- Radiator site gauge
- Komtrax™ Komatsu tracking system

Engine related parts

- Radiator reserve tank
- Heavy-duty radiator mask
- Cooling fan, hydrostatic driven
- Hard water area arrangement

incl. corrosion resistor

- Fuel tank inlet strainer
- Intake pipe with rain cap
- Dry type air cleaner, double element with dust indicator and evacuator
- Locks, filter caps and covers
- Starting motor 24 V/7,5 kW
- Alternator 24 V/50 A
- Batteries 2 × 12 V/140 Ah
- Gull wing engine side covers
- Hydroshift transmission
- Torque converter
- HSS hydrostatic steering system
- Auto-downshift function
- Quick shift selection system

Attachments

- Front pull hook
- Wiper rear window
- Wiper front window
- Wipers doors

- Underguards, oil pan and transmission
- Lighting system, front
- Lighting system, rear
- Tool kit

Work equipment

- Hydraulics for ripper (EX only)
- Hydraulics for dozing blades

Safety equipment

- Back-up alarm
- Warning horn
- Steel cab, meets ISO 3449 FOPS standards
- ROPS canopy for cab, meets ISO 3471 and SAE J1040, APR88 ROPS standards

OPTIONAL EQUIPMENT

Cab

- Radio-Cassette

Undercarriage

- Single grouser heavy-duty shoes (EX: 560 mm; 610 mm; 660 mm)
- Single grouser shoes (EX: 560 mm; 660 mm)
- Single grouser shoes for cold area (EX: 660 mm)

Engine related parts

- Cold area arrangement (-30°)
- Electric type engine oil and coolant heater
- Starting motor 24 V/11 kW
- Alternator 24 V/75 A
- Batteries 2 × 12 V/200 Ah
- Intake pipe with pre-cleaner

Attachments

- Rigid drawbar (EX)
- Ripper working light (EX)
- Additional working light, rear

Work equipment

- Straight tilt blade 5,2 m³ (EX)
- Semi-U blade single tilt 7,0 m³ (EX)
- Strengthened Semi-U blade single tilt 7,0 m³ (EX)
- Straight MAPT blade 4,0 m³ (EX)
- U blade single tilt 8,5 m³ (EX)
- Strengthened U blade single tilt 8,5 m³ (EX)
- Straight tilt blade 5,9 m³ (PX)
- Multishank parallelogram ripper (EX)

- Hydraulics for ripper (field installation kit)

Safety equipment

- Fire extinguisher
- First aid kit

Control systems

- Komatsu-Topcon machine control systems



Komatsu Europe International NV

Mechelsesteenweg 586
B-1800 VILVOORDE (BELGIUM)
Tel. +32-2-255 24 11
Fax +32-2-252 19 81
www.komatsueurope.com