

HYDRAULIC EXCAVATOR

STANDARD EQUIPMENT

- Komatsu SAA6D170E-5, 515 kW turbocharged common rail direct injection diesel engine, EU Stage IIIA compliant
- Double element type air cleaner with dust indicator and auto-dust evacuator
- Cooling fan: remote hydraulically driven variable speed, reversible
- Radiator & oil cooler with fly net
- Automatic fuel line de-aeration
- Alternator 24 V/60 A
- Batteries 2 × 12 V/220 Ah
- 2 × starter motor 24 V/11 kW
- Electronic Open-centre load sensing (E-OLSS) hydraulic system
- Auto-deceleration function
- Multi-function colour monitor with equipment management monitoring system (EMMS)
- Working mode selection system (power mode, economy mode)
- Heavy lift mode
- 2 mode boom control
- Shockless boom control
- Adjustable PPC wrist control levers with 3 button controls for arm, boom, bucket and swing
- PPC control levers and pedals for steering and travel
- In-line filter for hydraulics
- Hydrostatic, 2-speed travel system with automatic shift and planetary triple reduction final drives, and hydraulic travel and oil disc parking brakes
- Highly pressurised and tightly sealed viscous mounted cab with tinted safety glass windows, front window wiper with intermittent feature, floor mat, cigarette lighter and ashtray, bottle holder & magazine rack
- Automatic climate control system
- Fully adjustable suspension seat with retractable seat belt
- Rearview mirrors, left and right
- Step light with timer
- Working lights, 2 boom, 2 cab roof front, 1 cab bottom
- Automatic swing holding brake
- Corrosion resistor
- Counterweight 18.000 kg
- Track guiding guard (each side)
- Track frame undercover (centre)
- Travel motor guards
- Revolving frame under cover (heavy-duty)
- Machine cab handrails and catwalk
- Horn, air
- Lockable fuel cap and covers
- Audible travel alarm
- One-touch engine oil drainage
- PM service connectors
- Parts book and operator manual
- Standard colour scheme and decals
- Toolkit and spare parts for first service
- 700 mm wide double grouser shoes
- KOMTRAX™ Plus (Vehicle Health Monitoring System)

OPTIONAL EQUIPMENT

- Arms (Backhoe):**
 - 3.400 mm arm assembly
 - 3.400 mm HD arm assembly
 - 3.400 mm SP arm assembly
 - 4.500 mm arm assembly
 - 4.500 mm HD arm assembly
 - 5.700 mm arm assembly
- Arms (Loading shovel):**
 - 3.800 mm arm assembly
- Booms (Backhoe):**
 - 7.800 mm SP boom assembly
 - 9.100 mm boom assembly
- Booms (Loading shovel):**
 - 5.300 mm boom assembly
- Alternator 90 A/24 V
- Automatic greasing system (Lincoln 18 ltr)
- Cab with pull-up type front window
- Grease gun, air pump
- Interconnected horn and flashing light
- Radio
- 1.000 mm wide double grouser shoes
- Full length track roller guards
- Satellite communication system for KOMTRAX™ Plus



Komatsu Europe International NV

Mechelsesteenweg 586
B-1800 VILVOORDE (BELGIUM)
Tel. +32-2-255 24 11
Fax +32-2-252 19 81
www.komatsueurope.com