PC138US-10

Standard and Optional Equipment

FNGINE

LITORITE	
Komatsu SAA4D95LE-6 turbocharged common rail direct injection diesel engine	•
EU Stage IIIB/EPA Tier 4 interim compliant	•
Automatic engine warm-up system	•
Engine overheat prevention system	•
Fuel control dial	•
Auto-deceleration function	•
Engine key stop	•
Engine ignition can be password secured on request	•
Alternator 24 V/35 A	•
Starter motor 24 V/4,5 kW	•
Batteries 2 × 12 V/72 Ah	•

HYDRAULIC SYSTEM

Electronic closed-centre load sensing (E-CLSS) hydraulic system (HydrauMind)	•
Pump and engine mutual control (PEMC) system	•
One additional hydraulic circuit	•
6-working mode selection system; power mode, economy mode, breaker mode, attachment power and attachment economy mode, and lifting mode	•
Adjustable PPC wrist control levers for arm, boom, bucket and swing, with sliding proportional control for attachments and 3 auxiliary buttons	•
Prepared for hydraulic quick-coupler	•
Additional hydraulic functions	0

DRIVES AND BRAKES

Hydrostatic, 2-speed travel system with automatic	
shift and planetary gear type final drives, and	•
hydraulic travel and parking brakes	

PPC control levers and pedals for steering and travel

UNDERCARRIAGE

Track frame under-guards	•
500 mm triple grouser shoes	•
600, 700 mm triple grouser shoes	0
500 mm road-liner (rubber) shoes	0

CABIN

Reinforced safety SpaceCab™; highly pressurised and tightly sealed hyper viscous mounted cab with tinted safety glass windows, large roof window with sun shade, pull-up type front window with locking device, removable lower window, front window wiper with intermittent feature, sun roller blind, cigarette lighter, ashtray, luggage shelf, floor Heated, high back air suspension seat with lumbar support, console mounted height adjustable arm rests, and retractable seat belt Automatic climate control system 12/24 Volt power supplies Beverage holder and magazine rack Hot and cool box Radio Auxiliary input (MP3 jack) Lower wiper Rain visor (not with OPG)

SERVICE AND MAINTENANCE

Automatic fuel line de-aeration	•
Double element type air cleaner with dust indicator and auto dust evacuator	•
KOMTRAX [™] – Komatsu wireless monitoring system	•
Multi-function video compatible colour monitor with Equipment Management and Monitoring System (EMMS) and efficiency guidance	•
Toolkit	•
Komatsu CARE	•
0 1 11	_

WORK EQUIPMENT

Mono boom	0
2,5 m; 3,0 m arms	0
Dozer blade (with 500 or 600 mm shoes)	0
Komatsu buckets	0
Komatsu breakers	0

SAFETY EQUIPMENT

Rear view camera system	•
Electric horn	•
Overload warning device	•
Audible travel alarm	•
Boom safety valves	•
Large handrails, rear-view mirrors	•
Battery main switch	•
ROPS compliant to ISO 12117-2:2008	•
Emergency engine stop switch	•
Arm safety valve	•
OPG Level II front guard (FOPS), hinged type	0
OPG Level II top guard (FOPS)	0

LIGHTING SYSTEM

Working lights: 1 revolving frame and 1 boom (r.h.) Additional working lights: 5 cab roof, 1 boom (l.h.), 1 counterweight (rear), additional revolving frame (l.h.), beacon and harness for 2 lamps (not included) in boom foot area

OTHER EQUIPMENT

Remote greasing for swing circle and pins	•
Electric refuelling pump with automatic shut off function	•
Standard colour scheme and decals	•
Parts book and operator manual	•
Additional counterweight 500 kg	0

Further equipment on request

- standard equipment
- o optional equipment

Your Komatsu partner:



Komatsu Europe **International NV**

Mechelsesteenweg 586 B-1800 VILVOORDE (BELGIUM) Tel. +32-2-255 24 11

Fax +32-2-252 19 81 www.komatsu.eu

UENSS16600 10/2013

Materials and specifications are subject to change without notice. **KOMATSU** is a trademark of Komatsu Ltd. Japan.