Hydraulic Excavator **PC170LC-10**

Standard and Optional Equipment

ENGINE

Komatsu SAA4D107E-2A turbocharged common rail direct injection diesel engine	•
EU Stage IIIB/EPA Tier 4 interim compliant	٠
Suction type cooling fan with radiator fly screen	٠
Automatic engine warm-up system	٠
Engine overheat prevention system	٠
Fuel control dial	٠
Auto-deceleration function	٠
Engine key stop	٠
Engine ignition can be password secured on request	•
Alternator 24 V/60 A	٠
Starter motor 24 V/4,5 kW	٠
Batteries 2 \times 12 V/120 Ah	٠

HYDRAULIC SYSTEM

Electronic closed-centre load sensing (E-CLSS) hydraulic system (HydrauMind)	•
Pump and engine mutual control (PEMC) system	٠
One additional hydraulic circuit	٠
6-working mode selection system; power mode, economy mode, breaker mode, attachment power and attachment economy mode, and lifting mode	•
PowerMax function	٠
Adjustable PPC wrist control levers for arm, boom, bucket and swing, with sliding proportional control for attachments and 3 auxiliary buttons	•
Prepared for hydraulic quick-coupler	٠
Additional hydraulic functions	0

UNDERCARRIAGE

UNDERCARRIAGE	
Track roller guards	٠
Track frame under-guards	٠
LC undercarriage	•
500, 600, 700, 800 mm triple grouser shoes	0

CABIN

CABIN	
Reinforced safety SpaceCab TM ; highly pressurised and tightly sealed hyper viscous mounted cab with tinted safety glass windows, large roof window with sun shade, pull-up type front window with locking device, removable lower window, front window wiper with intermittent feature, sun roller blind, cigarette lighter, ashtray, luggage shelf, floor mat	•
Heated, high back air suspension seat with lumbar support, console mounted height adjustable arm rests, and retractable seat belt	•
Automatic climate control system	•
12/24 Volt power supplies	•
Beverage holder and magazine rack	•
Hot and cool box	٠
Radio	•
Auxiliary input (MP3 jack)	٠
Lower wiper	0
Rain visor (not with OPG)	0

SERVICE AND MAINTENANCE

Automatic fuel line de-aeration
Double element type air cleaner with dust indicator
and auto dust evacuator
KOMTRAX [™] – Komatsu wireless monitoring
system
Multi-function video compatible colour monitor with
Equipment Management and Monitoring System •
(EMMS) and efficiency guidance
Toolkit •
Komatsu CARE •
Service points O

WORK EQUIPMENT

Mono boom	0
2,25 m; 2,6 m; 2,9 m arms	0

SAFETY EQUIPMENT

٠
٠
٠
٠
٠
٠
٠
٠
٠
٠
0
0

DRIVES AND BRAKES

Hydrostatic, 2-speed travel system with automatic shift and planetary gear type final drives, and hydraulic lock service brakes	•
PPC control levers and pedals for steering and travel	•

LIGHTING SYSTEM

Working lights: 2 revolving frame, 1 boom	٠
Additional working lights: 4 cab roof (front), 1 cab roof (rear), 1 boom, 1 counterweight (rear), beacon	0

OTHER EQUIPMENT

Standard counterweight	٠
Remote greasing for swing circle and pins	٠
Electric refuelling pump with automatic shut-off function	•
Biodegradable oil for hydraulic system	0
Additional counterweight 3.500 kg	0

Further equipment on request

standard equipment

 $\,\circ\,$ optional equipment



Komatsu Europe International NV

Mechelsesteenweg 586 B-1800 VILVOORDE (BELGIUM) Tel. +32-2-255 24 11 Fax +32-2-252 19 81 www.komatsu.eu

Your Komatsu partner:

UK Distributor

Marubeni-Komatsu Ltd

Redditch, Worcestershire

01527 512 512

UENSS16900 06/2014

Materials and specifications are subject to change without notice. **KOMATSU** is a trademark of Komatsu Ltd. Japan.

www.marubeni-komatsu.co.uk

Printed in Europe – This specification sheet may contain attachments and optional equipment that are not available in your area. Www.marubeni-komatsu.co.uk Please consult your local Komatsu distributor for those items you may require. Materials and specifications are subject to change without notice.