

HYDRAULIC EXCAVATOR

STANDARD EQUIPMENT

- Komatsu SAA6D140E-5, 323 kW turbocharged common rail direct injection diesel engine, EU Stage IIIA compliant
- Double element type air cleaner with dust indicator and auto-dust evacuator
- Cooling fan: remote hydraulically driven variable speed, reversible
- Radiator & oil cooler with fly net
- Automatic fuel line de-aeration
- Alternator 24 V/75 A
- Batteries 2 × 12 V/170 Ah
- Starter motor 24 V/11 kW
- Electronic Open-centre load sensing (E-OLSS) hydraulic system
- Auto-deceleration function
- Automatic engine warm-up system
- Engine overheat prevention system
- Multi-function colour monitor with equipment management monitoring system (EMMS)
- Working mode selection system (power mode, economy mode, lifting mode)
- Pump and engine mutual control (PEMC) system
- Adjustable PPC wrist control levers with 3 button controls for arm, boom, bucket and swing
- PPC control levers and pedals for steering and travel
- In-Line filter for hydraulics
- PowerMax function
- Hydrostatic, 2-speed travel system with automatic shift and planetary triple reduction final drives, and hydraulic travel and oil disc parking brakes
- SpaceCab™; highly pressurised and tightly sealed viscous mounted cab with tinted safety glass windows, opening roof hatch with window pull-up type front window with locking device, removable lower window, front window wiper with intermittent feature, ashtray, luggage box, floor mat, cigarette lighter, sun roller blind, bottle holder & magazine rack
- Air conditioning
- Stereo radio cassette
- Step light with timer
- 12 Volt power supply
- Fully adjustable heated air suspension seat
- Track frame undercovers
- Beacon
- Additional cab roof lights
- Machine cab handrails and catwalk
- Remote greasing for swing circle and pins
- Lockable fuel cap and covers
- Full length track roller guards
- Parts book and operator manual
- Engine ignition can be password secured on request
- Standard colour scheme and decals
- 2 mode boom control
- Counterweight mirror
- KOMTRAX™ Komatsu Tracking System
- Audible travel alarm
- Toolkit and spare parts for first service

OPTIONAL EQUIPMENT

- Shoes:**
 - 600 mm triple grousers
 - 750 mm triple grousers
 - 900 mm triple grousers
 - 600 mm double grousers
- Arms:**
 - 2.900 mm
 - 3.500 mm (not available with 6.600 mm boom)
- Booms:**
 - 6.600 mm (w/o boom safety valves)
 - 7.300 mm (with boom safety valves)
 - 7.660 mm (with boom safety valves)
- HCU for breaker (only with 7.300 mm and 7.660 mm boom)
- Arm safety valve (only with 7.300 mm and 7.660 mm boom)
- Rain visor
- Bio oil
- OPG Level II top guard (FOPS)
- OPG Level II front guard (FOPS)
- Lower wiper
- Auto grease system



Komatsu Europe International NV

Mechelsesteenweg 586
 B-1800 VILVOORDE (BELGIUM)
 Tel. +32-2-255 24 11
 Fax +32-2-252 19 81
 www.komatsueurope.com