

Midi-Excavator

PC80MR-3

Standard Equipment

- ROPS (ISO 3471) / FOPS (ISO 10262) cab with heating
- Mono boom with cylinder protection
- 1.650 mm digging arm
- 450 mm steel shoes
- 2.250 mm blade
- Adjustable seat with safety belt
- KOMTRAX™ - Komatsu satellite monitoring system
- Instrumentation including:
 - hour meter
 - LCD fuel level indicator
 - LCD engine water temperature indicator
 - two travel speed
 - working mode selection
- indicators: air filter clogging, oil pressure, generator, hydraulic oil filter, engine pre-heating, selected speed
- Horn
- 12 V internal electric plug
- Working light on boom
- Hose burst valve on boom, arm and blade cylinders
- Overload warning device
- Travel acoustic alarm
- Double element air filter
- Rear-view mirror (right side)
- 1 / 2 way auxiliary hydraulic circuit
- Battery main switch

Optional Equipment

- Two-piece boom (with positioner)
- Air conditioning
- 2.000 mm digging arm
- 600 mm steel shoes
- Rubber shoes
- Roadliner shoes
- Rear working light on cab
- 1 front working light on cab
- 2 front working lights on cab
- Additional working light on boom
- Radio
- Lateral mirror (left side)
- Auxiliary hydraulic line for a 3 movements attachment
- Auxiliary line for hydraulic quick-coupler
- Bucket range (300 - 800 mm)
- 1.500 mm ditch cleaning bucket
- 1.650 mm ditch digging bucket (52°)
- Additional counterweight (230 kg)
- Rotating beacon
- Bucket linkage with lifting hook
- Final stop valves on equipment circuit
- Relieve valve for equipment circuit
- Refuelling pump

Your Komatsu partner:

KOMATSU

**Komatsu Europe
International NV**

Mechelsesteenweg 586
B-1800 VILVOORDE (BELGIUM)
Tel. +32-2-255 24 11
Fax +32-2-252 19 81
www.komatsu.eu

WESS005804 03/2012

Materials and specifications are subject to change without notice.
KOMATSU is a trademark of Komatsu Ltd. Japan.