

# Midi-Excavator

## PC88MR-8

### Standard and Optional Equipment

#### ENGINE

|  |   |
|--|---|
| Komatsu SAA4D95LE-5 common rail, multi injection, water cooled, turbocharged diesel engine, EU Stage IIIA/EPA Tier III compliant | ● |
| Alternator 24 V / 60 A   | ● |

#### UNDERCARRIAGE

|                         |   |
|-------------------------|---|
| 450 mm steel shoes      | ● |
| 600 mm steel shoes      | ○ |
| 450 mm rubber shoes     | ○ |
| 450 mm road liner shoes | ○ |
| Track roller guard      | ○ |

#### HYDRAULIC SYSTEM

|   |   |
|---|---|
| 5-working mode selection system; Power mode, economy mode, breaker mode, attachment mode and lifting mode | ● |
| One additional 2-way full-flow service valve with hydraulic line for attachment on boom and arm (HCU-A)   | ● |
| Additional auxiliary hydraulic circuit (HCU-B)  | ● |
| Relieve valve on service spool  | ● |
| 2nd auxiliary hydraulic circuit (HCU-C) + preparation for hydraulic quick-coupler                         | ○ |

#### LIGHTING SYSTEM

|                                  |   |
|----------------------------------|---|
| Working light on boom            | ● |
| Front working light on cab       | ○ |
| 4 front working lights on cab    | ○ |
| Rear working light on cab        | ○ |
| Additional working light on boom | ○ |

#### CAB

|                                  |   |
|----------------------------------|---|
| Automatic air conditioner        | ● |
| Adjustable seat with safety belt | ● |
| Large multi-lingual LCD monitor  | ● |
| Radio pre-setting                | ● |
| 12 V electric plug               | ● |
| Radio                            | ○ |

#### SERVICE AND MAINTENANCE

|   |   |
|---|---|
| Equipment Management and Monitoring System (EMMS) | ● |
| Double-element air filter                         | ● |
| KOMTRAX™ - Komatsu satellite monitoring system    | ● |
| Refuelling pump                                   | ○ |

#### SAFETY EQUIPMENT

|                                     |   |
|-------------------------------------|---|
| Overload warning device             | ● |
| Travel acoustic alarm               | ● |
| Horn                                | ● |
| Rear-view mirrors (left side, rear) | ● |
| Hose burst valve on boom cylinder   | ● |
| Arm safety valve                    | ● |
| Rotating beacon                     | ○ |
| Bucket linkage with lifting hook    | ○ |

#### ATTACHMENTS

|                                     |   |
|-------------------------------------|---|
| 2.320 mm blade                      | ● |
| Bucket range (350 - 750 mm)         | ○ |
| 1.500 mm ditch cleaning bucket      | ○ |
| 1.650 mm ditch digging bucket (52°) | ○ |

#### OTHER EQUIPMENT

|  |   |
|--|---|
| Mono boom with cylinder protection                         | ● |
| 1.650 mm digging arm                                       | ● |
| Automatic 2-speed travel                                   | ● |
| Auto deceleration  | ● |
| Proportional roll switch on joystick for equipment circuit | ● |
| Two-piece boom (with positioner)                           | ○ |
| 2.100 mm digging arm (for mono boom)                       | ○ |
| 1.900 mm digging arm (for two-piece boom)                  | ○ |
| Additional counterweight (218 kg)                          | ○ |

Further work equipment, accessories and special application arrangements on request

Other attachments on request

- standard equipment
- optional equipment

Your Komatsu partner:

# KOMATSU

**Komatsu Europe  
International NV**  
Mechelsesteenweg 586  
B-1800 VILVOORDE (BELGIUM)  
Tel. +32-2-255 24 11  
Fax +32-2-252 19 81  
[www.komatsu.eu](http://www.komatsu.eu)

WESS006203 03/2012

Materials and specifications are subject to change without notice.  
**KOMATSU** is a trademark of Komatsu Ltd. Japan.