Midi-Excavator **PW118MR-8**

Standard and Optional Equipment

ENGINE

| Komatsu SAA4D95LE-5 common rail, multi |
|--|
| injection, water cooled, turbocharged diesel engine, |
| EU Stage IIIA/EPA Tier III compliant |
| Alternator 24 V / 60 A |

| TYRES | |
|----------------------|---|
| Twin tyres 9-20 | • |
| Single tyres 18-19.5 | 0 |

HYDRAULIC SYSTEM

| 5-working mode selection system; Power mode, economy mode, breaker mode, attachment mode and lifting mode | • |
|---|---|
| One additional 2-way full-flow service valve with hydraulic line for attachment on boom and arm (HCU-A) | • |
| Additional auxiliary hydraulic circuit (HCU-B) | ٠ |
| Relieve valve on service spool | ٠ |
| 2nd auxiliary hydraulic circuit (HCU-C) + preparation for hydraulic quick-coupler | 0 |
| Final lock valves on attachment circuit | 0 |
| | |

LIGHTING SYSTEM

| Working light on boom | • |
|----------------------------------|---|
| Front working light on cab | 0 |
| 4 front working lights on cab | 0 |
| Rear working light on cab | 0 |
| Additional working light on boom | 0 |

CAB

| CAB | |
|----------------------------------|---|
| Automatic air conditioner | • |
| Adjustable seat with safety belt | • |
| Large multi-lingual LCD monitor | ٠ |
| Radio pre-setting | • |
| 12 V electric plug | • |
| Radio | 0 |
| Rain visor | 0 |
| | |

SERVICE AND MAINTENANCE

| Equipment Management and Monitoring System (EMMS) | • |
|--|---|
| Double-element air filter | • |
| KOMTRAX [™] - Komatsu satellite monitoring system | • |
| Refuelling pump | 0 |
| | |

SAFETY EQUIPMENT

| Overload warning device | ٠ |
|-------------------------------------|---|
| Travel acoustic alarm | • |
| Horn | • |
| Rear-view mirrors (left side, rear) | ٠ |
| Hose burst valve on boom cylinder | • |
| Arm safety valve | • |
| Rotating beacon | 0 |
| Bucket linkage with lifting hook | 0 |

ATTACHMENTS

| Stabilisers and/or blade with safety valve | • |
|--|---|
| Bucket range (300 - 1.000 mm) | 0 |
| 1.800 mm ditch cleaning bucket | 0 |
| 2.100 mm ditch digging bucket (45°) | 0 |

Further work equipment, accessories and special application arrangements on request

Other attachments on request

OTHER EQUIPMENT Two-piece boom (with positioner)

Proportional roll switch on joystick for equipment

Oscillating front axle with manual cylinder locking

2.000 mm digging arm

Automatic parking brake

1.850 mm digging arm

Additional counterweight (388 kg)

4-wheel steering

Auto deceleration

circuit

Swing lock

•

•

٠

٠

•

۲

•

•

•

0

- standard equipment
- optional equipment

Your Komatsu partner:



Komatsu Europe

International NV Mechelsesteenweg 586 B-1800 VILVOORDE (BELGIUM) Tel. +32-2-255 24 11 Fax +32-2-252 19 81 www.komatsu.eu

WESS007401 03/2012

Materials and specifications are subject to change without notice. **KOMATSU** is a trademark of Komatsu Ltd. Japan.