

# Wheel Loader

# WA430-6

## Standard and Optional Equipment

### ENGINE

Komatsu SAA6D114E-3 turbocharged common rail direct injection diesel engine	●
EU Stage IIIA/EPA Tier III compliant	
Fuel filter with water separator	●
Engine cooling fluid corrosion resistor	●
Alternator 60 A/24 V	●
Starter motor 5,5 kW/24 V	●
Batteries 143 Ah/2 × 12 V	●

### CHASSIS AND TYRES

Heavy-duty axles	●
Front fenders	●
Limited-slip differential (LSD) front and rear	○
Tyres 23.5 R25; 26.5 R25, 750/65 R25	○
Full rear fenders	○

### SAFETY EQUIPMENT

Emergency steering system	●
Horn	●
Vandalism protection	●
Back-up alarm	●
Battery main switch	●
Handrails on left/right	●
Front screen protective grid	○
Beacon light	○
Electronic anti-theft lock	○
Roof rail	○
Roof rail and step light	○
Rear view camera system	○
Additional convex rear view mirror	○
Optical back-up alarm (strobe light)	○
Back-up alarm (white noise version)	○

### LIGHTING SYSTEM

2 halogen main headlights	●
2 spotlights at front and rear	●
Reversing light	●
Additional lights front and rear	○
Xenon working lights	○

### CABIN

Spacious double door driver's cab to DIN/ISO	●
ROPS/FOPS frame according to SAE	●
Air-suspended, heated seat	●
Air conditioner	●
CD radio	●
Hot and cool box	●
All-round tinted glazing	●
Front laminated glass	●
Heated rear window	●
Rear window wiper	●
Sun visor	●
Adjustable steering column	●
12 V power supply	○
Fire extinguisher	○
Sun roller blind	○
Automatic climate control system	○
Super DeLuxe seat	○

### TRANSMISSION AND BRAKES

Electronically controlled ECMV automatic transmission with mode selector and variable transmission cut-off	●
Working mode selection system	●
Large-capacity torque converter	●
Torque converter lock-up	○
Joystick steering with integrated F/R transmission function, 2-stage	○
20, 25 or 30 km/h speed limitation (not with torque converter lock-up)	○

### HYDRAULIC SYSTEM

2-spool main control valve	●
PPC fingertip control, two levers	●
Automatic return-to-dig	●
3-spool main control valve	○
PPC control, 1-lever (Multi-function lever) with integrated F/R transmission function	○
Electronic 2-lever control (EPC) including:	
- Bucket stop modulation	○
- Boom stop pre-setting	
- Semiautomatic dig function	
Biodegradable oil for hydraulic system	○

### SERVICE AND MAINTENANCE

Hydrostat-driven radiator fan with automatic reversing function	●
EMMS (Equipment Management Monitoring System) with self-diagnostic function and maintenance display	●
KOMTRAX™ - Komatsu satellite monitoring system	●
Tool-set	●
Automatic central lubrication	●
Filling tool for central lubrication system	○
Turbo II air pre-cleaner, cyclone type	○

### OTHER EQUIPMENT

Counterweight	●
Electronically controlled load stabilizer (ECSS)	●
Special custom colour	○
Add. counterweight 325 kg	○
Additional side counterweight 430 kg	○
Anti-corrosion specification	○
Waste-handler specification	○
Cold area kit (engine and cab pre-heating)	○

### ATTACHMENTS

High-lift equipment	○
Hydraulic quick-coupler	○
Universal buckets	○
Earthmoving buckets	○
Stock pile buckets	○
High-dump buckets	○
Log grapples	○
Fork carrier and tines	○
Waste handling buckets	○
Light material buckets	○

Further equipment on request

The WA430-6 is equipped in accordance with the safety regulations of the machinery guidelines 89/392 EWG ff and EN474.

- standard equipment
- optional equipment

Your Komatsu partner:

# KOMATSU

**Komatsu Europe  
International NV**  
Mechelsesteenweg 586  
B-1800 VILVOORDE (BELGIUM)  
Tel. +32-2-255 24 11  
Fax +32-2-252 19 81  
[www.komatsu.eu](http://www.komatsu.eu)

VESS001106 07/2011

Materials and specifications are subject to change without notice.  
**KOMATSU** is a trademark of Komatsu Ltd. Japan.