

WHEEL LOADER

STANDARD EQUIPMENT

Engine

- Komatsu SAA12V140E-3 engine, EPA Tier II compliant
- Alternator 90 A/24 V
- Batteries 160 Ah/12 V × 4
- Starter motor 7,5 kW/24 V × 2
- Water separator

Cab

- ROPS/FOPS frame to SAE
- Air conditioner
- Electronic display/monitoring system (EDIMOS II)
- Air-suspended seat with seat belt
- Advanced Joystick Steering System (AJSS)
- Washer, front & rear
- Wiper, front & rear, front intermittent
- Rear-view mirrors
- Sun visor

Powertrain

- Electronically controlled transmission (3F, 3R)
- Hydraulically activated oil cooled disc service brakes
- Dry disc parking brake
- Full-floating axles

Hydraulics

- 2-spool main control valve
- Bucket positioner
- Automatic boom kick-out

Machine

- Automatic shift control
- Active power-up system (two stage hydraulics)
- In-line filter
- Power train underguard

Others

- Standard boom
- Counterweight (WA900-3)
- Corrosion resistor
- Front fenders
- Rear access stairs
- PM service connectors
- KOMTRAX™ Plus (Vehicle Health Monitoring System)

Safety

- Back-up alarm
- Electric horn
- Emergency steering
- Emergency brake
- Rear under view mirror
- Side working light

Tyres

- 45/65 R45 radial tyres

Lights

- 2 front working lights
- 2 head lights
- Reverse lights
- Stop and tail lights
- Turn signal with hazard switch (2 front, 2 rear)

OPTIONAL EQUIPMENT

Engine

- Batteries 200 Ah (C200)
- Engine shut off mechanical
- Radiator core protection grid
- Radiator anti-clogging type

Cab

- Tilttable steering wheel
- Joystick steering (in conjunction with steering wheel)
- Radio-cassette

Tyres

- Rims for 45/65-45 tyres
- Bias and radial ply tyres
- Tyre inflation kit

Buckets

- Special buckets on request

Others

- Counterweight 1.600 kg (WA800-3)
- Satellite communication system for KOMTRAX™ Plus

Machine

- Counterweight, additional (1.600 kg) for high-lift arrangement (WA800-3)
- Counterweight for high-lift arrangement (2.900 + 1.400 + 1.600 kg) (WA900-3)
- Fuel tank with fast fill coupler
- Auto greasing
- Boom for high-lift arrangement
- Boom for Load & Carry arrangement (WA800-3)
- Cold area arrangement (-30 °C to 40 °C)
- Remote boom positioner (WA800-3)

Safety

- Fog lamp
- Fire extinguisher
- Beacon light



**Komatsu Europe
International NV**

Mechelsesteenweg 586
B-1800 VILVOORDE (BELGIUM)
Tel. +32-2-255 24 11
Fax +32-2-252 19 81
www.komatsu.eu