Rigid Backhoe Loader

WB93R-5

Standard Equipment

- Komatsu EU Stage IIIA compliant turbo engine
- Komtrax Komatsu satellite monitoring system
- Power Shuttle transmission with 4 synchronised gears
- Load sensing, variable displacement axial piston pump
- · Side-by-side radiator
- · 4 wheel drive
- Electro-hydraulic 100% differential lock
- · Declutch switch
- Foot pedal and hand control accelerator
- Horn
- . Maintenance free battery 155 Ah
- 12 V external electric plug

- 12 V internal electric plug
- Antifreeze (-36 °C)
- Front and rear working lights
- Road homologation
- · Lights for road travel
- Rotating beacon
- External rear-view mirror (left)
- ROPS/FOPS cab with heater and fan
- Tinted glass
- · Adjustable steering column
- · Adjustable seat with safety belt
- Front and rear washer and windshield wipers
- Internal storage compartments (one lockable)
- Cup holder
- Sun visor
- · Fully opening bonnet

- · External lockable toolbox
- Dry type air cleaner with clogging indicator
- Fuel filter with integrated water separator
- Gauges & indicators: transmission oil temperature, 4WD engagement, brake oil level, differential lock, fuel level, hour meter, pre-heating, engine speed, engine coolant temperature, engine oil pressure, air filter clogging
- Safe position seat sensor
- PPC lock switch
- Front tyres: 12.5/80 R18 10 PR
- \bullet Rear tyres: 16.9 \times 28 12 PR
- Backhoe boom and arm safety valves, overload warning device (for EU countries only)

LOADER

- PPC servo-controls
- Speed-up function
- · Heavy duty safety bar
- Self-levelling
- General purpose bucket with standard teeth

BACKHOE

- Mechanical control levers
- Power/Economy working modes
- Electro-hydraulic backhoe boom lock
- Backhoe swing transport lock
- Electro-hydraulic backhoe slide frame release lock
- PPC servo-controls for stabilisers
- · Hydraulic cushions

Optional Equipment

- · Air conditioning
- Additional front counterweights (150 kg, 375 kg)
- Deluxe pneumatic suspension seat
- · Drive shaft guard (front)
- Cold area arrangement (-30 °C) with 185 Ah battery and pre-heating systems
- High ambient/altitude arrangement
- TÜV + TBG version (20 km/h or 40 km/h)
- Battery disconnection safety switch
- Rubber pads for stabilisers
- Hose burst valves:
- loader arm
- backhoe boom and arm safety valves, overload warning device (for non-EU countries only)
- stabilisers
- Biodegradable hydraulic oil
- Hydraulic hand hammer circuit
- Hydraulic oil filter clogging indicator

WESS004509 11/2012

- Air cyclone pre-filter
- Refuelling pump

- · Additional rear-view mirror (right)
- Four additional working lights on cab
- Radio pre-setting
- Radio
- Backup alarm
- Front mudguards
- Front tyres:
- 365/70 R18
- 320/80 R18 IT 530
- 12.5 20 MPT 10 PR
- Rear tyres:
- 18.4 × 26 12 PR
- 440/80 R28 IT 530
- 16.9 30 IND 10 PR

LOADER

- LSS (Load Stabiliser System)
- Safety valve deactivation switch
- · Auxiliary hydraulic circuits:
- floating function
- front auxiliary hydraulic circuit
- floating and "Return-To-Dig" function
- additional front auxiliary hydraulic circuit (6-way valve)

- Attachments:
- bolt-on cutting edge
- cutting edge on teeth
- flip-over forks on 4×1 bucket
- forks (for quick-coupler)
 hydraulic and mechanical quick-coupler
- 4×1 bucket with pre-setting for flip-over forks and angle opening indicator
- general purpose bucket (for quickcoupler)
- 4×1 bucket (for quick-coupler)
- dozer blade
- snow blade
- hand hammer
- heavy duty 4×1 bucket

BVCKHUE

- PPC servo controls
- Alternative control pattern
- Hydraulic backhoe side shiftAuxiliary hydraulic circuits:

- 2-way circuit for attachments (auger, tilting bucket)
- hammer circuit
- Offset boom
- Telescopic arm
- Offset boom and telescopic arm
- Attachments:
- ditch cleaning bucket (1.400 mm)
- full range of buckets (300 mm - 900 mm)
- ditch digging bucket (1.000 mm)
- mechanical quick-coupler
 (for std buckets)
- hydraulic hammer
- Bucket linkage with lifting hook

Your Komatsu partner:



Komatsu Europe International NV

Mechelsesteenweg 586 B-1800 VILVOORDE (BELGIUM) Tel. +32-2-255 24 11 Fax +32-2-252 19 81

www.komatsu.eu

Materials and specifications are subject to change without notice. **KOMATSU** is a trademark of Komatsu Ltd. Japan.