Rigid Backhoe Loader **WB97R-5**

Standard Equipment

- Komatsu EU Stage IIIA compliant turbo engine
- Komtrax Komatsu satellite monitoring system
- Full Power Shift transmission with automatic shift and kick-down function
- Load sensing, variable displacement axial piston pump
- Side-by-side radiator
- 4 wheel drive
- Deluxe mechanical suspension seat
- Electro-hydraulic 100% differential
- lock

 Declutch switch
- Foot pedal and hand control accelerator
- Horn
- Maintenance free battery 155 Ah

- 12 V external electric plug
- 12 V internal electric plug
- Antifreeze (-36 °C)
- Front and rear working lights
- Road homologation
- Lights for road travel
- Rotating beacon
- Rear-view mirrors
- ROPS/FOPS cab with heater and fan
 Tinted global
- Tinted glass
 Adjustable steering
- Adjustable steering columnAdjustable seat with safety belt
- Cup holder
- Front and rear washer and windshield
- wipers
- Internal storage compartments (two lockable)
- Sun visor
- Radio pre-setting

Optional Equipment

- Air conditioning
- Additional front counterweights (150 kg, 375 kg)
- Deluxe pneumatic suspension seat
- Drive shaft guard (front)
- Cold area arrangement (-30 °C) with 185 Ah battery and pre-heating systems
- High ambient/altitude arrangement
 TÜV + TBG version
- (20 km/h or 40 km/h)
- Battery disconnection safety switch
- Rubber pads for stabilisers
- Hose burst valves:
- loader arm
- backhoe boom and arm safety valves, overload warning device (for non-EU countries only)
- stabilisers
- Biodegradable hydraulic oil
- Hydraulic hand hammer circuit

Your Komatsu partner:

· Hydraulic oil filter clogging indicator

WESS004609 11/2012

- Air cyclone pre-filter
- Refuelling pump
- Four additional working lights on cab
- Radio Backup alarm
- Front mudguards
- Front tyres:
- 365/70 R18
- 320/80 R18 IT 530
- 12.5 20 MPT 10 PR
- Rear tyres:
- 18.4 × 26 12 PR
- 440/80 B28 IT 530
- 16.9 30 IND 10 PR

LOADER

- LSS (Load Stabiliser System)
- Safety valve deactivation switch
- Auxiliary hydraulic circuits:
- floating function
- front auxiliary hydraulic circuit
- floating and "Return-To-Dig" function

- Fully opening bonnet
- External lockable toolbox
- Dry type air cleaner with clogging indicator
- Fuel filter with integrated water separator
- Gauges & indicators: transmission oil temperature, 4WD engagement, brake oil level, differential lock, fuel level, hour meter, pre-heating, engine speed, engine coolant temperature, engine oil pressure, air filter clogging
- · Safe position seat sensor
- PPC lock switch
- Front tyres: 12.5/80 R18 10 PR
- Rear tyres: 16.9 × 28 12 PR
- Backhoe boom and arm safety valves, overload warning device (for EU countries only)

LOADER

- PPC servo-controls
- Speed-up function
- Heavy duty safety bar
- Self-levelling
- General purpose bucket with standard teeth

BACKHOE

- PPC servo-controls
- Power/Economy working modes
- Electro-hydraulic backhoe boom lock
- Backhoe swing transport lock
- Electro-hydraulic backhoe slide frame release lock
- PPC servo-controls for stabilisers

Alternative control pattern

· Hydraulic backhoe side shift

- 2-way circuit for attachments (auger,

· Offset boom and telescopic arm

- ditch cleaning bucket (1.400 mm)

- ditch digging bucket (1.000 mm)

- bucket linkage with lifting hook

KOMATSU

· Auxiliary hydraulic circuits:

tilting bucket)

- hammer circuit

Telescopic arm

· Attachments:

- full range of buckets

(for std buckets)

- hydraulic hammer

Komatsu Europe International NV Mechelsesteenweg 586 B-1800 VILVOORDE (BELGIUM)

Tel. +32-2-255 24 11 Fax +32-2-252 19 81 www.komatsu.eu

KOMATSU is a trademark of Komatsu Ltd. Japan.

Materials and specifications are subject to change without notice.

(300 mm - 900 mm)

- mechanical quick-coupler

Offset boom

Hydraulic cushions

BACKHOF

- additional front auxiliary hydraulic circuit (6-way valve)
- Attachments:

coupler)

- dozer blade

- snow blade

Printed in Europe – This specification sheet may contain attachments and optional equipment that are not available in your area. Please consult your local Komatsu distributor for those items you may require. Materials and specifications are subject to change without notice.

- hand hammer

- bolt-on cutting edge
- cutting edge on teeth
- 4×1 bucket with pre-setting for flip-over forks and angle opening indicator
- flip-over forks on 4×1 bucket
- hydraulic and mechanical quickcoupler

- general purpose bucket (for quick-

- 4×1 bucket (for quick-coupler)

- forks (for quick-coupler)

- heavy duty 4×1 bucket